

DECLARATION OF CONFORMITY

ARTIC INDUSTRIAL QUIMICA SA certifies as a manufacturer:

Paint:

ARTIDUR A -2C-. Aliphatic polyurethane enamel, solvent-based and two-component, highly versatile.

Intended uses for this product:

Ideal for painting concrete floors. Perfect as a metal finish for rust protection. Very useful as an enamel for any hard surface in the home. Offers excellent weather resistance.

Limitations:

All supports must be clean, dry (<4% moisture on concrete), hard and cohesive.

According to several Standardized Standards related to the functionality of the paint and carrying out several tests in the specialized and accredited laboratories of APLUS (LGAI TECHNOLOGICAL CENTER) and OTEC (Joaquín Riera Tuebols, SA), the following results and characteristics are offered:

Essential features	Benefits	Test standard
Direct traction adhesion	4.5 MPa	UNE-EN 48274:2003
Taber Abrasion (Cs-10, m=1Kg, 500 cycles)	80 mg	UNE-EN 48274:2003
Flexibility (3mm Tapered Mandrel)	None observed cracks	UNE-EN 48274:2003
Resistant to water, mild solvents, weak acids and bases	None observed defects	UNE-EN 48274:2003
Slip resistance (with addition of ANTISKID PLUS)	C1, C2 and C3	UNE-EN 16165 Annex C
Fire behavior in walls and ceilings	Ds1d0	EN 13501-1:2018
Fire behavior in soils	Bfls1	EN 13501-1:2018

And to attest to this, this document is issued and signed in Balaguer on October 30, 2025.



Elisabet Biel
 General Directorate